

HUB-xxxxxx(B)-> get interface ethernet0/0.99

Interface ethernet0/0.99(VSI):

description ethernet0/0.99

number 0, if_info 792, if_index 99, VLAN tag 99, mode nat

link inactive, phy-link up/full-duplex

vsys Root, zone Admin, vr trust-vr, vsd 0

dhcp client disabled

admin mtu 1500, operating mtu 1500, default mtu 1500

*ip 172.x.x.254/24 mac 0010.dbff.2000

manage ip 172.x.x.252, mac 001f.122f.f400

route-deny disable

pmtu-v4 enabled

ping enabled, telnet disabled, SSH enabled, SNMP enabled

web enabled, ident-reset enabled, SSL enabled

DNS Proxy disabled, webauth disabled, g-arp enabled, webauth-ip 0.0.0.0

OSPF enabled BGP disabled RIP disabled RIPng disabled mtrace disabled

PIM: not configured IGMP not configured

MLD not configured

NHRP disabled

bandwidth: physical 0kbps, configured egress [gbw 0kbps mbw 0kbps]

configured ingress mbw 0kbps, current bw 0kbps

total allocated gbw 0kbps

DHCP-Relay enabled, server 172.x.x.110 (VPN encryption)

DHCP-server disabled

HUB-xxx(B)-> exec nsrp sync global-config check-sum

HUB-xxx(B)-> Warning: configuration out of sync